



PL Solutions Photoluminescent Running Man Signs
2 Foot Candles (22 lux)
120 Minute Minimum Rated



Project Name: _____
 Type of Project: _____
 Prepared By: _____
 Approved By: _____

Features

- Eligible for Carbon Credits
- Zero energy consumption—zero cost, green design Zero maintenance—no bulbs, no battery replacement Non-toxic, non-radioactive
- No disposal costs
- Designed for surface flag, ceiling or conduit mounting.
- Can be used for both high-level and low-level applications.
- Easily movable if egress path changes
- Thin, low profile construction.
- Consistent, uniform illumination 50 ft. rated, visibility, readability.
- Recyclable: LEED Qualified point contributor

Technical Information

Sizes available:

- RM- No Arrow Framing System (10 x 17in x 0.75in) (25.4cm x 43.18cm x 1.9cm)
- *RM without arrow is used over doors*
- RM with Arrow Framing System (17.24in x 10in x 0.75in) (43.8cm x 25.4cm x 1.9cm)
- *RM with arrow is used to show the direction of egress*
- Background: Photoluminescent—Yellow
- Tint Lettering/Image: Screen Printed Image
- Flat Illumination: High Visibility Green
- Visibility: 15.25 meters (50 feet) for a **MINIMUM OF 120 MINUTES**
- Durability: Explosion-proof for areas requiring explosion-proof exit signage

Tests Passed:

- CAN/ULC S-572 – UL924 – UL1994
- *Standard for Photoluminescent and Self Luminous Exit Signs and Path Marking Systems*
- Meets NBC 2010/2015
- Meets ISO 7010 Pictogram *Graphical symbols - Safety Signs in Workplaces and Public Areas*
- Rated for 120 Minute Listing for LED, Fluorescent, Metal Halide, Mercury Vapor

GUARANTEE: 25+ years

Power Requirements


No backup electrical support required – CAN-ULC-S 572 Rev 2

Installation


Surface, flag, ceiling or stem mounted.

Before installation it must be determined that there is a minimum of 2Fc (22 lux) of light on face(s) of the sign at all times during

Photoluminescent Background



Ceiling Mount Option



Wall Mount Option



Image				
Silver Canopy Aluminum Frame	RUNNING MAN-NA	RUNNING MAN-RA	RUNNING MAN-LA	RUNNING MAN-DB
Description	Single Sided	Right Facing, Single Sided	Left Facing, Single Sided	Double Sided

www.globalplsolutions.com

PL Solutions Inc. 337 Beach Blvd., Unit #5, Hamilton, ON L8H 6W4 416-540-4944